



Color Variants
VP230114
Stainless steel control panel
Width 28 cm

Included accessories
2 x spatula.

VP230114
Vario Teppan Yaki 200 series
Stainless steel control panel
Width 28 cm

Can be combined with the cooktops of the Vario 200 series to a harmonic unity
Generous control panel for comfortable and secure operation
Cooking directly on the metal surface, without any pots or pans
Exact temperature control up to 240 °C
Keep warm setting

Cooking zones
Useable area: W 22.5 x D 39.5 cm.

Handling
Keep warm setting.
Electronic temperature control from 120 °C to 240 °C.
Cleaning stage.

Features
Heating element with 1800 W.
Stainless steel frame seamlessly welded with the stainless steel surface.


Safety
Pre-heat and residual heat indicator.
Operation indicator.

Planning notes
The distance from the upper edge of the work surface to the upper edge of the intermediate shelf must be at least 150 mm.
Appliance can be snapped into the worktop from above.
A minimum lateral clearance of at least 30 mm from adjacent heat-sensitive furniture or contact surfaces must be observed or thermal insulation fitted.
Intermediate shelf required; after installation, this shelf must only be removed using tools to guarantee the touch protection from below.
Appliance weight: approx. 10.

Connection
Total connected load 1.8 KW.
Connecting cable 1.7 m without plug.

Characteristics
Product name/family
Vario/Domino Teppan Yaki
Built-in / Free-standing
Built-in
Energy input
Electric
Type of control
Electronic
Grill grating material
Min. required niche size for installation (HxWxD)
135 x 268 x 490
Width of the appliance
288
Dimensions (HxWxD)
135 x 288 x 523
Dimensions of the packed product (HxWxD)
223 x 407 x 603
Net weight
9.6
Gross weight
10.7
Residual heat indicator
separate
Location of control panel
Hob front
Basic surface material
Color of surface
Stainless steel, Stainless steel
Color of frame
Stainless steel
Length electrical supply cord
170
EAN code
4242006190958
Electrical connection rating
1800
Gas connection rating
Fuse protection
10
Voltage
220-240
Frequency
50; 60
Included accessories
2 x spatula

Consumption and connection features
2022-11-22
Page 1



Mounting rail
(rear and front)

